

[illegible]

BRAND: AWAB**Tech Tip:**

All critical hose connections should be double clamped at both ends. Ideally, the hose clamp screws should be mounted opposite one another for maximum security. Use the highest quality AWAB hose clamps for longest life and best performance.

RANGE**RANGE**

Item No.	SAE SIZE	Minimum (inch)	Maximum (inch)	mm	Fits Hose Size
AWA-316012	Mini	29/64	33/64	-	-
AWA-319014	3 (3/8" Wide)	5/16	9/16	8-14	1/4", 5/16" & 3/8" fuel
AWA-319017	4	7/16	3/4	11-17	3/8", 1/2" fuel
AWA-316020	6	1/2	13/16	13-20	5/8"
AWA-316024	8	5/8	15/16	15-24	1/2"
AWA-316028	10	3/4	1-1/8	19-28	1/2 and 5/8 250 hose
AWA-316032	12	7/8	1-1/4	22-32	1"
AWA-316038	16	1-1/16	1-1/2	26-38	1-1/4"
AWA-316044	20	1-1/4	1-3/4	32-44	1-1/2"
AWA-316050	24	1-1/2	2	38-50	1-3/4"
AWA-316057	28	1-1/4	2-1/4	32-57	1-7/8'
AWA-316064	32	1-1/2	2-1/2	38-64	2"
AWA-316070	36	1-3/4	2-3/4	44-70	2-1/4"
AWA-316076	40	2	3	51-76	2" ID
AWA-316083	44	2-1/4	3-1/4	57-83	2-3/4"
AWA-316089	48	2-1/2	3-1/2	64-89	3"
AWA-316095	52	2-3/4	3-3/4	70-95	3-1/4"
AWA-316102	56	3	4	76-102	3-1/2"
AWA-316108	60	3-1/4	4-1/4	83-108	3-3/4"
AWA-316114	64	3-1/2	4-1/2	89-114	4"
AWA-316127	72	3-1/2	5	89-127	4-1/2"
AWA-316140	80	4	5-1/2	102-140	4-3/4"
AWA-316152	88	4-1/2	6	114-152	5"
AWA-316165	96	5	6-1/2	127-165	5-1/2"
AWA-316178	104	5-1/2	7	140-178	6"
AWA-316191	112	6	7-1/2	152-191	6-1/2"
AWA-316203	120	6-1/2	8	165-203	7"
AWA-316308	186	10-5/8	12-1/8	270-308	